

Hybrid Adaptor & Bare Fiber Adaptor

Fiber adaptor is one kind of fiber flanges to be used for the interconnection between two fiber connectors. UPC and APC polishing are available to be selected. For interconnecting fiber connectors, there are two kinds of fiber adaptors, mating sleeve and hybrid adaptor.

Hybrid adaptor is used in interconnecting of two different connectors so that it is widely applied in optical fiber management system, optical testing project, ODN, FTTx, Metro, CATV.

Bare fiber adaptor is a special hybrid adaptor for 0.25mm bare fiber (tight buffer coating) to form an adaptor quickly. Bare fiber adaptor is widely applied in field testing, ODF and ODN project.

Features

- Easy to use
- Easy to be installed in ODN equipments
- High reliability
- Low insertion loss
- Zirconia internal tube
- Large operating and temperature range
- Customized packaging and configuration
- Full Telcordia GR1209/1221 qualifications

Specification

Connector Type	FC SC LC ST DIN E2000 MU MTRJ
Polishing Mode	UPC or APC
Insertion Loss	< 0.2dB
Interchangeability	< 0.2dB
Durability	> 1000 times
Repeatability	< 0.1dB
Working Temp	-40 ~ +80°C
Working Humidity	< 90%RH




Description

Hybrid adaptor, FC & ST UPC, simplex, rectangle shape, zirconia internal tube, metal material



Description

Hybrid adaptor, FC & LC UPC, simplex, rectangle shape, zirconia internal tube, metal material




Description

Hybrid adaptor, FC & SC UPC, simplex, rectangle shape, zirconia internal tube, metal material



Description

Hybrid adaptor, SC & LC UPC, simplex, rectangle shape, zirconia internal tube, metal material



Description

Hybrid adaptor, SC & ST UPC, simplex, rectangle shape, zirconia internal tube, metal material



Description

Bare fiber adaptor, FC UPC, single mode, zirconia internal tube, metal material



Description

Bare fiber adaptor, LC UPC, single mode, zirconia internal tube, metal material



Description

Bare fiber adaptor, SC UPC, single mode, zirconia internal tube, metal material



Description

Bare fiber adaptor, ST UPC, single mode, zirconia internal tube, metal material