

## Fiber Optical Splice Closure **GJS-D001**

### Description

DOME type fiber optic splice closure is also called as vertical closure, it is suitable for FTTH accessing. The input and output are on the same side. An oval hole and three round holes facilitates the operation. It is suitable for aerial, underground, conduct installation.

### Features

- Heat shrinkable sealing structure.
- High quality industrial plastic body material.
- One oval hole and three round holes for cable entrance.
- Suitable for cable diameter 5mm-25mm. .
- Support aerial,underground,pipeline,man holes,hand holes
- Protection level reaches IP68.
- 360 degrees access, fiber bending > 40mm.
- Maximum capacity: 96F single or 144F ribbon.
- Number of trays: 4 pcs x 24F.



### Configuration

Material	Field Size	Max Capacity		Cable Entrance	Weight	Color
Strengthen Polymer Plastic	H*D(mm) 440*190	Splice Cores 96 Cores	Trays 4x24F	1 x oval port 3 x round port	2.3kg	Black

### Application

- Aerial cable installation
- Pole mounted installation
- Wall mounted installation
- Man hole and hand hole installation
- FTTH access layer

### Standard Accessories

installation bolts and nuts, Protection sleeves, Cable entry rubber, Cable tube.

### Optional Accessories

Bracket for wall,pole,pressure valve...etc.