

Fiber Optical Splice Closure GJS-D021

Description

DOME type fiber optic splice closure is also called as vertical closure, it is suitable for FTTH accessing. The input and output are on the same side. An oval hole and eight round holes facilitates the operation. It is suitable for aerial, underground, conduct installation.

Features

- Heat shrinkable sealing structure.
- High quality industrial plastic body material.
- One oval hole and eight round holes for cable entrance.
- Suitable for cable diameter 5mm-38mm. .
- Support aerial, underground, pipeline, man holes, hand holes
- Protection level reaches IP68.
- 360 degrees access, fiber bending > 40mm.
- Maximum capacity: 144F single or 432F ribbon.
- Number of trays: 6 pcs x 24F.



Configuration

Material	Field Size	Max Capacity		Cable Entrance	Weight	Color
Strengthen Polymer Plastic	H*D(mm) 470*210	Splice Cores 144 Cores	Trays 6x24F	1 x oval port 8 x round port	2.3kg	Black

Application

- Aerial cable installation
- Pole mounted installation
- Wall mounted installation
- Man hole and hand hole installation
- FTTH access layer

Standard Accessories

installation bolts and nuts, Protection sleeves, Cable entry rubber, Cable tube.

Optional Accessories

Bracket for wall, pole, pressure valve...etc.