

FATB-0216R Fiber Access Terminal-16 Cores

Description

FATB-0216R fiber access termination box is able to hold up to 16 subscribers and 120 splicing point. It is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

Features

- Water-proof design with IP-65 Protection level.
- Integrated with flap-up splice trays.
- Maximum 120F splice capacity, stainless anti-rust bolts and nuts.
- Easy for maintenance and expansion, neat cabling.
- Fiber bend radius control more than 40mm.
- 180 degree access with buckled lock structure.
- 2pcs of 1*8 PLC splitter can be installed.
- 16 pcs of pre-installed reinforced water-proof adapter for SC..
- 1 mid-span cable entrance(10-16.5mm) for uncut cable.



Configuration

Material	Size	Max Capacity		Reinforced Adapter	Weight	Color
PC+ABS	A*B*C(mm) 340*220*95	Splice 120 Fibers (5 trays,24 fiber/tray)	PLC Splitter 2pcs of 1x8	16 pcs SC/UPC or SC/APC	1.85kgs	Grey/Black

Application

- Wall-mounted Installation
- Pole-mounted Installation
- Aerial-hanging Installation
- Suitable for Huawei Pre-connectorized drop cable with reinforced connector

Standard Accessories

Splice tray and cable management tool, installation nuts and bolts, protection sleeves, hose clamp, cable tube, key, wrench, rubber seal for cable entrance.

Optional Accessories

Pole mounted kits.