

FATB-0424S Fiber Access Terminal-24 Cores

Description

FATB-0424S fiber access termination box is able to hold up to 24 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

Features

- Water-proof design with IP-65 Protection level.
- Integrated with splice tray and cassette adapter holder.
- Maximum 12F splice capacity, stainless anti-rust bolts and nuts.
- Easy for maintenance and expansion, neat cabling.
- Fiber bend radius control more than 40mm.
- 180 degree access with buckled lock structure.
- 3pcs of 1*8 PLC splitter can be installed.
- 24 pcs of mechanical ports for 3-7mm drop cable.
- 1 mid-span cable entrance(10-16.5mm) for uncut cable and 2 reserved cable entrances for distribution cable gland(8-13.5mm).



Configuration

Material	Size	Max Capacity		Nos of Adapter	Weight	Color
PC+ABS	A*B*C(mm) 340*220*95	Splice 12 Fibers	PLC Splitter 3pcs of 1x8(SC)	24 pcs SC/UPC or SC/APC	1.85kgs	Grey/Black

Application

- Wall-mounted Installation
- Pole-mounted Installation
- Aerial-hanging Installation
- Suitable for 2x3mm indoor FTTH drop cable and outdoor 4-7mm figure-8 self-supporting drop cable

Standard Accessories

Splice tray and cable management tool, installation nuts and bolts, protection sleeves, hose clamp, cable tube, key, wrench, rubber seal for cable entrance.

Optional Accessories

Pole mounted kits.